CAT6 U/UTP 23 AWG CABLE

Description/Order Information

كابل CAT6 U/UTP 4 أزواج مجدولة, موصل
نحاس صلب مصمت AWG23 مع سترة
غلاف PVC/LSZH, أبيض ,ورمادي.
التغليف: 305 متر - كابل في كرتونة

part No :C6-U23-010
part No :C6L-U23-010
Cat 6 U/UTP, 4 twisted pairs, Solid Copper
23 AWG with PVC/LSZH Sheathing, White , Gray.
Packaging: 305 m - Coil in Box

Standard Compliance

- **EN 50173:2007 EN 50288-3-1:2013**
- **ISO/IEC 11801 First Edition - 2017**
- **ISO/IEC 11801 Second Edition - 2017**
- **UL444, UL1581, UL1666**
- **Flame Test: IEC 60332-1, IEC 60332-3C**
- **TIA/EIA 568 C-2**
- **Pass fluke > 90 m , Fluke Test 8000**



Applications

- **10 BASE-T (Ethernet)**
- **100 BASE-T (Fast Ethernet)**
- **1000 BASE-T (Gigabit Ethernet)**
- **100 Mbps TP-PMD (ANSI X3T9.5)**
- **155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM**
- **4/16 Token Ring, POE**
- **ISDN, Voice, Videos, digital and analogue data transmission up to 250 MHz**
- **Supporting up to 90 metres**
- **Flame retardance: LSZH**
- **Operation temperature: -20 °C to 70 °C**

CAT6 U/UTP 23 AWG CABLE

Construction

- **Conductor: 23 AWG Solid Copper, diameter 0.56 (+/- 0.005) mm**
- **Copper Purity 99.99%**
- **Insulation: HDPE, diameter 1.02 (+/- 0.03) mm**
- **Pairs: 4 Twisted Pairs on Central PE cross**
- **Sheath: PVC/LSZH, 0.55 (+/- 0.05) mm thick, White, Gray**
- **Outer Diameter: 6.3 mm**

Packing Unit

- **Unit of Package 1: PCE**
- **Number of unit in package: 1**
- **Package weight: 15 kg**
- **Package height: 40 cm**
- **Package width: 26.5 cm**
- **Package length: 41 cm**



Sustainability features

- **Toxic heavy metal free: YES**
- **Mercury free: YES**

CAT6 U/UTP 24 AWG CABLE

Description/Order Information

Part No : C6-U24-011
Part No : C6L-U24-011
Cat 6 U/UTP, 4 twisted pairs, Solid Copper
24 AWG with PVC/LSZH Sheathing, White , Gray.
Packaging: 305 m - Coil in Box

كابل CAT6 U/UTP 4 أزواج مجدولة, موصل
نحاس صلب مصمت AWG24 مع سترة
غلاف PVC/LSZH, أبيض ,ورمادي.
التغليف: 305 متر - كابل في كرتونة

Standard Compliance

- **EN 50173:2007 EN 50288-3-1:2013**
- **ISO/IEC 11801 First Edition - 2017**
- **ISO/IEC 11801 Second Edition - 2017**
- **UL444, UL1581, UL1666**
- **Flame Test: IEC 60332-1, IEC 60332-3C**
- **TIA/EIA 568 C-2**
- **Pass fluke > 90 m , Fluke Test 8000**



Applications

- **10 BASE-T (Ethernet)**
- **100 BASE-T (Fast Ethernet)**
- **1000 BASE-T (Gigabit Ethernet)**
- **100 Mbps TP-PMD (ANSI X3T9.5)**
- **155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM**
- **4/16 Token Ring, POE**
- **ISDN, Voice, Videos, digital and analogue data transmission up to 250 MHz**
- **Supporting up to 90 metres**
- **Flame retardance: LSZH**
- **Operation temperature: -20 °C to 70 °C**

CAT6 U/UTP 24 AWG CABLE

Construction

- **Conductor: 24 AWG Solid Copper, diameter 0.53 (+/- 0.005) mm**
- **Copper Purity 99.99%**
- **Insulation: HDPE, diameter 1.02 (+/- 0.03) mm**
- **Pairs: 4 Twisted Pairs on Central PE cross**
- **Sheath: PVC/LSZH, 0.55 (+/- 0.05) mm thick, White, Gray**
- **Outer Diameter: 6.3 mm**

Packing Unit

- **Unit of Package 1: PCE**
- **Number of unit in package: 1**
- **Package weight: 14 kg**
- **Package height: 40 cm**
- **Package width: 26.5 cm**
- **Package length: 41 cm**



Sustainability features

- **Toxic heavy metal free: YES**
- **Mercury free: YES**